









HERRINGBONE DROPLOC

Traditionally the storied herringbone pattern originated with the Romans, who laid bricks in this pattern to create strong, stable roads. Lately, this pattern was used in flooring when it enjoyed immense popularity which was typically installed in castles, palaces, official residences, and stately homes across Europe. This popular parquet design is achieved using wood blocks cut to shape and then laid diagonally to create the 'herringbone' pattern. With the new technology now we can achieve the herringbone design using luxury vinyl tile and SPC rigid vinyl which is mainly made of polyethylene and calcium carbonate with a certain percentage. Polyethylene is an environmentally non-toxic renewable resource. All the ingredients are non-toxic, non-radioactive and eco-friendly. Herringbone DropLoc vinyl flooring is a design choice for residential and commercial spaces due to its incredible durability and resilience but most importantly its impressive realistic appearance.

Features

Resilient and Flexibility

Vinyl material has a very good performance of resilience and flexibility compare with wood parquet, which allows herringbone DropLoc floor board to fit better to the sub-ground as the environment change.

Super Water Resistant

LVT/SPC vinyl core board is totally water-proof material compare to hardwood parquet, without the worry of damage or staining from water and moisture and counteracts the accidents that happen in our busy lives.


Perfect Acoustic Resistant

Completely avoid the walking acoustic and the terrible friction noise comes from the installation gap which is frequently happened from wood floor, plus with the super anti-sliding performance, these are the unique advantages of herringbone DropLoc flooring.

Easy for Installation

Herringbone DropLoc vinyl flooring can be easily installed with international patented click locking system, It's very simple and convenient to work and quick to lay, lends itself perfectly to both DIY and professional installation.

Recommended Layout



Zigzag Style **Parquet Style**

Groove Tongue Tongue

About DropLoc

Applied with international patented drop-locking technology, Herringbone DropLoc brings the fashionable and elegant "herringbone" design appearance, while bringing a new DIY installation experience.There are two kinds of patterns called "A plank" and "B plank" which has opposite directional locking system, they have to be fixed following the pointed direction during the installation.

^{*} Parquet layout requires the length of the floor panel has to be multiple times to the width.









Product's Parameter

Recommended Size	615x128mm, 936x150mm	
Thickness	4.0/5.0 mm	
Wearlayer	0.2/0.3/0.5 mm	
Surface Texture	Mat/Crystal/Wood Embossed	
Installation Method	DropLoc	

Technical Specification

Item	Standard	Result
Overall Thick	EN ISO 24236	±0.15mm
Wearlayer Thick	EN ISO 24340	±0.05mm
Squareness	EN 434	<0.3mm
Dimensiontal Stability after exposure to heat	EN ISO 24342	X Direction: <0.1% Y Direction: <0.05%
Curling after exposure to heat	EN 434	<0.1mm
Peeling Strength	EN 431	>60N(50mm)
Residual Indentation	EN ISO 24343-1	<0.1mm
Castor Chair	ISO 4918	After 25000 cycles, no visible damage
Slip Resistance	EN 13893	Class DS
Fire Resistance	EN 13501-1	BfI-S1
Abrasion Resistance	EN 660	Group T
Stain & Chemical Resistance	EN ISO 26987	Class 0
Cigatette Burn Test	EN ISO 1399	Class 4
Color Fastness	ISO 105-B02	≥Grade 6
Formaldehyde Emission	EN 717-3	0





Recommended Designs







1107 6118-3







6118-20B 6115-6A 6178-2A

^{*} The scanned design might be variation. The exact color should be confirmed with physical samples.



Recommended Designs









S192 S203









S257 S238

^{*} The scanned design might be variation. The exact color should be confirmed with physical samples.